

STACKER DOOR

COMMERCIAL SERIES

Stacker doors offer an exceptionally wide opening for easier entertaining & ventilation. Available with 3 or 6 panels, they have a slim profile

- *Door heights up to 3050mm are possible
- *100kg rated rollers run on a separate (anodised) 'chevron' profiled track for smooth & reliable operation
- *Horizontal head rollers help stabilise such large panels
- *The standard locks feature anti-lift pins (*top right x2*)
- *An optional architectural handle is shown at *bottom right*
- *Reveals can be primed or raw hardwood, or for 'square set'
- *Aluminium reveals are optional for a 'commercial' look
- *An optional stacking fly screen runs on its own tracks
- *Screen mesh can be fibreglass, heavy-duty fibreglass or stainless steel for bushfire prone areas
- *A spreader bar(s) is fitted to screens wider than 1200mm



The smooth, flat sill is only 50mm high, & can be rebated to create a flush threshold




Standard handles come in black, white or silver



Architectural handles come in black, white or satin chrome

STACKER DOOR

COMMERCIAL SERIES



NOTE: ALL SIZES ARE TYPICAL RATHER THAN DEFINITIVE. ANY WIDTH OVER 6000mm WILL REQUIRE THE FRAME TO BE JOINED ONSITE, WHICH WILL INCUR EXTRA COST. NOTE THAT FLY SCREEN DOORS OVER 1200mm WIDE WILL REQUIRE A SPREADER BAR TO RETAIN TENSION, & SUCH SCREENS WITH STAINLESS STEEL MESH MAY HAVE 2x SPREADER BARS DUE TO THEIR HEIGHT

Sizing

Door style & opening detail should be considered as viewed externally

Sizes indicated are the overall door size. For Stud openings add 20mm to both height & width

Glazing

Glazing strength to minimum N3 rating

Glazing to be grade A safety glass. Maximum double glazed panel thickness is 24.76mm

Certification

Performance data is available for this product on request

Specify

Frame colour, configuration, height, width & depth, reveal type (incl. for plaster reveals, or aluminium only)

Optional: interlocker type, handle type & colour, dummy handle (architectural handle only),

patio bolt & colour, fly screen, mesh type, sill flap, glass type

The above product sizes comply with structural requirements (AS2047-2014, *Windows and external glazed doors in buildings*) for an 'N3' wind rating (AS4055-2012, *Wind loads for housing*).

This is typical of sites *outside* of suburban areas. The Terrain Category could be as low as 1, have a Topographic Class of 2 & have very little shielding by way of other buildings or tall vegetation such as trees surrounding it.

Please specify if your site has different characteristics to any of those listed. Your building professional (architect, designer, surveyor, engineer, builder, etc.) can often assist with such determinations.